



## COUPLINGS

### Zero-Flex Rigid Couplings

- Angled pad design for rigidity
- Rated up to 750 psi/5170 kPa
- Sizes from 1 – 12"/25 – 300 mm



### Flexible Couplings

- Allows expansion, contraction and deflection
- Rated to 1000 psi/6900 kPa
- Sizes from 3/4 – 12"/15 – 600 mm



### AGS Couplings

- Robust two-piece housing
- Revolutionary wider wedge shaped groove
- Rated up to 350psi/2400 kPa
- Sizes from 14-24"/350-600 mm



### Copper Coupling

- Used to join copper tubing
- Rated up to 300 psi/2065 kPa
- Sizes from 2 – 8"/50 – 200 mm



### Flange Adapters

- Designed to prevent rotation
- Hinged for easy handling
- ANSI Class 125, 150 and 300
- Sizes from 2-24"/50-600 mm



## FITTINGS & HOLE CUT

### Original Grooved Fittings



### AGS Fittings



### Grooved Copper Fittings



### Mechanical-T<sup>®</sup> Bolted Branch Outlets and Crosses



### Vic-Let<sup>™</sup> Strapless Outlet



### Vic-O-Well<sup>™</sup> Strapless Thermometer Outlet



## VALVES

### Vic-300 MasterSeal Butterfly Valves

- Bi-directional shut-off
- Dead end service to full working pressure
- Pressure enhanced rubber seat reduces torque
- Rated to 300 psi/2065 kPa
- Sizes from 2-12"/50 – 300 mm



### AGS Butterfly Valves

- Offers excellent flow with low torque operation
- Coated for corrosion resistance
- Rated to 300 psi/2065 kPa
- Sizes from 14 – 24"/350 – 600 mm




### Vic-Check Valves

- Includes hydrodynamically efficient profile
- Installation in both horizontal and vertical positions
- Rated to 300 psi/2065 kPa
- Sizes from 2 1/2 – 12"/65 – 300 mm
- AGS also available in sizes 14 – 24"/350 – 600 mm



### Tour & Andersson Balancing Valves

- Allows for precision flow balancing & measurement
- Isolation/positive shut-off valve
- Drain/Fill/Vent connection
- Rated up to 300 psi/2065 kPa
- Sizes from 1/2 – 12"/13 – 300 mm



## ACCESSORIES

### Suction Diffusers

- Provides optimum flow conditions
- Provided with removable strainer and fine mesh sleeve
- Rated to 300 psi/2065 kPa
- Sizes from 3x2"/80x50 mm – 12x12"/300x300 mm



### Strainers

- Provides straight-through flow for lower pressure drop
- Easy basket removal for cleaning
- Rated to 750 psi/5170 kPa
- Sizes 1 1/2 – 12"/40 – 300 mm



### AGS Suction Diffusers & Strainers

- Provides optimum flow conditions
- Provided with removable strainer and fine mesh sleeve
- Rated to 300 psi/2065 kPa
- Suction diffuser sizes from 14x10"/350x250 mm – 24x24"/600x600 mm
- Strainer sizes from 14 – 24"/350 – 600 mm



### Clearflow Dielectric Waterway

- Eliminates corrosion of dissimilar metals in the presence of water
- For pressures up to 300 psi/2065 kPa
- Sizes from 1/2 – 8"/15 – 200 mm



### Field Portable Roll Groovers



### Field Fabrication Roll Groovers



### Plant/Shop Fabrication Roll Groovers



### Hole Cutting Tools



### Vic-Tap II



For details on the entire Victaulic Product Line, please consult the G-103 Product Catalog or visit [www.victaulic.com](http://www.victaulic.com)



NORTH AMERICA · UNITED KINGDOM · EUROPE  
MIDDLE EAST · LATIN AMERICA · ASIA PACIFIC

[www.victaulic.com](http://www.victaulic.com)



WCAS-6XQPJV

Victaulic is a registered trademark of Victaulic company. ©2007 Victaulic company. All rights reserved. PB-293 4677 Rev. A Sku#WCAS-6XQPJV

**victaulic**<sup>®</sup>

Piping. Systems. Solutions.